



Corrigendum

Refer NIT no. 2914/VDP-Khapri/CE(E)/NRDA/2011-12, Raipur dated 20/05/2011 and read as follows, in Page 6 of 44 of Sl. No. 14(a) (i)

Sl. No.	In place of	Read As
14	Close Graded Premix Surfacing / Mixed Seal Surfacing (Mechanical means using HMP of appropriate capacity not less than 60 tonnes/hour. Providing, laying and rolling of close-graded premix surfacing material of 20 mm thickness using penetration grade bitumen to the required line, grade and level to serve as wearing course on a previously prepared base, including mixing in a suitable plant, laying and rolling with a Smooth wheeled roller 8-10 tonne capacity, and finishing to required level and grade.0000) a. with CRMB 60 i. Type B (13.2 mm to 0.09 mm size aggregates)	Close Graded Premix Surfacing / Mixed Seal Surfacing (Mechanical means using HMP of appropriate capacity not less than 60 tonnes/hour. Providing, laying and rolling of close-graded premix surfacing material of 20 mm thickness using penetration grade bitumen to the required line, grade and level to serve as wearing course on a previously prepared base, including mixing in a suitable plant, laying and rolling with a Smooth wheeled roller 8-10 tonne capacity, and finishing to required level and grade.) a. With 60/70 grade bitumen i. Type B (13.2 mm to 0.09 mm size aggregates)