



Corrigendum No. 4

Refer NIT no. 2914/VDP-Khapri/CE(E)/NRDA/2011-12, Raipur dated 20/05/2011 and read as follows, in Volume I & II –Tender Drawings & Price Tender

Sl. No. /Page No	In place of	Read As
8 / Page 3 of 44	Water Bound Macadam (Providing, laying, spreading and compacting stone aggregates of specific sizes to water bound macadam specification including spreading in uniform thickness, hand packing, rolling with vibratory roller 8-10 tonnes in stages to proper grade and camber, applying and brooming requisite type of screening/ binding Materials to fill up the interstices of coarse aggregate, watering and compacting to the required density.) a) Grading- II (Using Screening Crushable type such as Moorum or Gravel) i) Using Screening Type-B (11.2mm Agg.)	Water Bound Macadam (Providing, laying, spreading and compacting stone aggregates of specific sizes to water bound macadam specification including spreading in uniform thickness, hand packing, rolling with vibratory roller 8-10 tonnes in stages to proper grade and camber, applying and brooming requisite type of screening/ binding Materials to fill up the interstices of coarse aggregate, watering and compacting to the required density.) a) Grading- II (Using Screening Crushable type such as Moorum or Gravel) (i) Using Screening Crushable type such as Moorum or Gravel
8 / Page 4 of 44	Quantity = 3700 cum	Quantity = 2220 cum
11 / Page 4 of 44	Dense Graded Bituminous Macadam (Providing and laying dense bituminous macadam with 60-90 TPH HMP using crushed aggregates of specified grading, premixed with bituminous binder @ 4.0 to 4.5% by weight of total mix of mix and filler, transporting the hot mix to work site, laying with a hydrostatic paver finisher with sensor control to the required grade, level and alignment, rolling with smooth wheeled, vibratory and tandem rollers to achieve the desired compaction as per MORTH specification clause No. 507 complete in all respects.) a) With sensor paver finisher i) For Grading I (40 mm nominal size, bitumen content 4.0%)	Dense Graded Bituminous Macadam (Providing and laying dense bituminous macadam with 60-90 TPH HMP using crushed aggregates of specified grading, premixed with bituminous binder @ 4.0 to 4.5% by weight of total mix of mix and filler, transporting the hot mix to work site, laying with a hydrostatic paver finisher with sensor control to the required grade, level and alignment, rolling with smooth wheeled, vibratory and tandem rollers to achieve the desired compaction as per MORTH specification clause No. 507 complete in all respects.) a) With mechanical paver finisher i) For Grading I (40 mm nominal size, bitumen content 4.0%)

Sl. No. /Page No	In place of	Read As
13 / Page 5 of 44	Bituminous Concrete (Providing and laying bituminous concrete with 60-90 TPH hot mix plant using crushed aggregates of specified grading, premixed with bituminous binder @ 5.0 to 6.0% of mix and filler, transporting the hot mix to work site, laying with a hydrostatic paver finisher with sensor control to the required grade, level and alignment, rolling with smooth wheeled, vibratory and tandem rollers to achieve the desired compaction as per MORTH specification clause No. 509 complete in all respects) a. With sensor paver finisher i. for Grading I (19 mm nominal size) with CRMB 60- 5.5 %	Bituminous Concrete (Providing and laying bituminous concrete with 60-90 TPH hot mix plant using crushed aggregates of specified grading, premixed with bituminous binder @ 5.0 to 6.0% of mix and filler, transporting the hot mix to work site, laying with a hydrostatic paver finisher with sensor control to the required grade, level and alignment, rolling with smooth wheeled, vibratory and tandem rollers to achieve the desired compaction as per MORTH specification clause No. 509 complete in all respects) a) With mechanical paver finisher (i) for Grading II (13 mm nominal size) with bitumen 6.0 %
116 /Page 44 of 44	New Item	Water Bound Macadam (Providing, laying, spreading and compacting stone aggregates of specific sizes to water bound macadam specification including spreading in uniform thickness, hand packing, rolling with vibratory roller 8-10 tonnes in stages to proper grade and camber, applying and brooming requisite type of screening/ binding Materials to fill up the interstices of coarse aggregate, watering and compacting to the required density.) b) Grading- III (Using Screening Crushable type such as Moorum or Gravel) (i) Using Screening Crushable type such as Moorum or Gravel
116 /Page 44 of 44	New Item Quantity	1480 cum
Drawing No. NRDA-PSC-RD-TD-32004 &32002	WMM	WBM